



Technical Data **Submersible Motor - 4CS2606M**

Revision no.

Page:
1

Receiver


From

Company name
 Respons. Department
 Person in charge
 Phone number
 Fax no
 E-mail address



Brand: Gol Pumps
Model: 4CS2606M
Material: Stainless Steel 304

Dimensions (mm):



H	Cable		Weight
in.	Length (ft.)	AWG	lb.
12.1"	3.9	14	20

Project

Project ID

Created by

Created on

Last update



Part List and Materials

Submersible Motor - 4CS2606M

Revision no.

Page:


2

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Motor Model	P2		S.F	Voltage	Phase	Wire	In	I _{max}	I _{start}	PF (%)		Efficiency (%)		RPM	Thrust	Capacitor
	kW	HP		V	PH		A	A	A	Allowable Load	Overload Factor	Allowable Load	Overload Factor		N	UF
4CS2606M	0.37	0.5	1.6	115	Single	2	7.1	9.3	26.9	0.94	0.97	50.8	58.8	3450	2000	45UF 250V



NO.	Component	4CS
1	Upper/Lower Bracket	AISI 304
2	Stator Shell	AISI 304
3	Shaft	AISI 420
4	Seal Cover	Nylon
5	Lip Seal	NBR
6	Diaphragm	NBR
7	Sand Slinger	NBR
8	Lead Wire (Cable)	XLPE
	Bolts and Screws	AISI 304
	Lead Potting	Epoxy
	Thrust Pad	AISI 420

Project

Project ID

Created by

Created on

Last update