



Technical Data

Submersible Motor - 4CS6396

Revision no.

Page:

1

Receiver


From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address



Brand: Gol Pumps
Model: 4CS6396
Material: Stainless Steel 304

Dimensions (mm):



H	Cable		Weight
in.	Length (ft.)	AWG	lb.
27.7"	8.2	14	64

Project

Project ID

Created by

Created on

Last update



Part List and Materials

Submersible Motor - 4CS6396

Revision no.

Page:


3

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Motor Model	P2		S.F	Voltage	Phase	In	I _{max}	I _{start}	PF (%)		Efficiency (%)		RPM	Thrust
	kW	HP		V	PH	A	A	A	Allowable Load	Overload Factor	Allowable Load	Overload Factor		N
4CS6396	5.5	7.5	1.15	460	Three	10.9	12.1	78.3	0.79	0.83	79.1	78.7	3450	6000



NO.	Component	4CS
1	Upper/Lower Bracket	AISI 304
2	Stator Shell	AISI 304
3	Shaft	AISI 420
4	Seal Cover	Nylon
5	Lip Seal	NBR
6	Diaphragm	NBR
7	Sand Slinger	NBR
8	Lead Wire (Cable)	XLPE
	Bolts and Screws	AISI 304
	Lead Potting	Epoxy
	Thrust Pad	AISI 420

Project

Project ID

Created by

Created on

Last update