



Technical Data

Submersible Pump - ST 13-35

Revision no.

Page:

1

Receiver


From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address



Brand: Gol Pumps
Model: ST 13-35
Material: Noryl

Dimensions:



Outlet	Dimensions (inch)			Weight lb.
	A	B	C	
NPT 1 1/4"	33.7"	1 1/4"	3.9"	18.9

Project

Project ID

Created by

Created on

Last update



Performance Curves

Submersible Pump - SP 13-35

Revision no.

Page:


2

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Pump Model	Motor		Q Capacity 3500RPM								
			Gal/Min	0	7.9	9.2	10.6	13.2	15.9	18.5	21.1
	kW	HP	Head in Feet	1073	1024	997.4	958	866.1	731.6	574.1	383.9
	ST 13-35	3.7									



Project

Project ID

Created by

Created on

Last update



Part List and Materials Submersible Pump - SP 13-35

Revision no.


Page:

3

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address



No.	Part Name	Materials
1	Discharge Head	AISI 304
4	Check Valve Cone	AISI 304
6	Check Valve Retaining Ring	AISI 304
8	Bearing Spider	Glass Filled Polycarbonate
12	Diffuser	Glass Filled Polycarbonate
13	Bowl	AISI 304
18	Impeller	Noryl
34	Strainer	AISI 304
40	Pump Shaft / Coupling	AISI 304
42	Shaft Sleeve	AISI 304 or Norly
48	Pump Casing	AISI 304
52	Cable Guard	AISI 304
86	O-Ring	NBR
92	Bearing	Polyacetal

Project

Project ID

Created by

Created on

Last update