



Technical Data

Submersible Pump - ST 55-22

Revision no.

Page:

1

Receiver


From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address



Brand: Gol Pumps
Model: ST 55-22
Material: Noryl

Dimensions:



Outlet	Dimensions (inch)			Weight lb.
	A	B	C	
NPT 2"	55.5"	2"	3.9"	29.3

Project

Project ID

Created by

Created on

Last update



Performance Curves

Submersible Pump - SP 55-22

Revision no.


Page:
2

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Pump Model	Motor		Q Capacity 3500RPM														
			Gal/Min	0	21.1	23.8	26.4	31.7	37	42.3	47.6	52.8	58	63.4	68.7	74	79.3
ST 55-22	kW	HP	Head in Feet	627	555	545	532	512	489	459	430	387	348	299	246	180	115



Project

Project ID

Created by

Created on

Last update



Part List and Materials Submersible Pump - SP 55-22

Revision no.


Page:

3

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address



No.	Part Name	Materials
1	Discharge Head	AISI 304
4	Check Valve Cone	AISI 304
6	Check Valve Retaining Ring	AISI 304
8	Bearing Spider	Glass Filled Polycarbonate
12	Diffuser	Glass Filled Polycarbonate
13	Bowl	AISI 304
18	Impeller	Noryl
34	Strainer	AISI 304
40	Pump Shaft / Coupling	AISI 304
42	Shaft Sleeve	AISI 304 or Norly
48	Pump Casing	AISI 304
52	Cable Guard	AISI 304
86	O-Ring	NBR
92	Bearing	Polyacetal

Project

Project ID

Created by

Created on

Last update