

PRESSURE TANKS FOR POTABLE WATER AND PUMP SYSTEMS WITH REPLACEABLE BLADDER



model number	max. working pressure 145 psi capacity gallons	precharge pressure 30 psi NPT connection (stainless steel)	max. working temperature 210°F dimensions D x H. (inches)	q.ty per pallet
IL005763S4000000	1,30	1"	6.3 x 12.8	210
IL008763S4000000	2,10	1"	7.9 x 13	144
IL012763S4000000	3,20	1"	10.6 x 12.2	84
IL019763S4000000	5,00	1"	10.6 x 16.3	56
IL025763S4000000	6,60	1"	11.4 x 18.1	63
IL040763S4000000	10,60	1"	12.6 x 22.8	36
BL060762S4000000	16	1"	15 x 32.7	15
BL080762S4000000	21	1"	17.7 x 31.1	15
BL100762S4000000	26,5	1"	17.7 x 35.8	15
BL200S62S4000000	53	1" 1/2	22 x 49.2	8
BL300S62S4000000	79	1" 1/2	24.4 x 54	8
BL500S62S4000000	132	1" 1/2	30.7 x 57.5	1
HR020762S4000000	5,30	1"	11 x 19.7	56
HR040762S4000000	10,60	1"	13.8 x 23.6	36
HR060762S4000000	15,80	1"	16.1 x 26.8	20

Use for pump systems and hot and cold potable water

Pressure tanks approved by IAPMO Z1089-2013

Bladder approved by NSF/ANSI 61

VAREM SPA IS AN ITALIAN MANUFACTURER OF EXPANSION TANKS WITH A DISTRIBUTION NETWORK COVERING OVER 100 COUNTRIES AROUND THE WORLD.



Render of the tanks



Spare bladders and spare flanges available on demand.



WWW.GOLPUMPS.COM

